



DESCRIPTION OF ELEMENTS

- ① PAVEMENT (PCC OR AC)
- ② OPEN GRADED BASE COURSE MATERIAL (DRAINAGE LAYER)
THIS MATERIAL SHOULD HAVE A MINIMUM OF 2 FRACTURED FACES
- ③ CURB AND GUTTER
- ④ COLLECTION TRENCH – CENTERLINE OF COLLECTOR PIPE SHALL
BE LOCATED A MINIMUM OF 2 FEET BEHIND THE BACK OF CURB
AND GUTTER. THE SLOTTED COLLECTION PIPE SHALL BE INSTALLED
WITH SLOTS POINTED DOWN, WITH A MINIMUM 4 INCH CLEARANCE
BETWEEN THE COLLECTOR PIPE AND THE TRENCH WALLS AND BOTTOM
- ⑤ PERFORATED COLLECTION PIPE
- ⑥ OUTLET PIPE MARKER
- ⑦ OUTLET PIPE WITH AUTOMATIC DRAINAGE GATE
- ⑧ FILTER FABRIC
- ⑨ OUTLET PIPE

DRAWN BY: JSH
CHECKED BY: WGH

APPROVED BY:
DIRECTOR OF PUBLIC WORKS

CITY OF BOULDER, COLORADO
PORTLAND CEMENT
CONCRETE PAVEMENT

ISSUED: JULY 2, 1998
REVISED: OCT. 17, 2000

DRAWING NO.
2.71.A