



DRAINAGE SWAIL WHERE NECESSARY

BACKFILL EDGE WITH TOPSOIL. FINISHED GRADE TO BE FLUSH WITH PATH EDGE (TYPICAL). RESTORE LANDSCAPING TO PRE-EXISTING CONDITION.

PREPARED SUBGRADE: COMPACTED ROADBASE OR USE ON-SITE GRAVEL MATERIAL WHERE APPROVED BY THE ENGINEER. OVER EXCAVATE IF UNSTABLE SUB SOILS ARE ENCOUNTERED AND REPLACE WITH SUITABLE FILL MATERIAL. COMPACT ALL FILL AREAS TO 95% STANDARD PROCTER AT 2% OPTIMUM MOISTURE. REMOVE ALL TOPSOIL PRIOR TO SUBGRADE PREPARATION.

6" THICK (MIN) CONCRETE. APPLY BROOM FINISH PERPENDICULAR TO PATH. SAWCUT $\frac{1}{4}$ " JOINTS, 1 $\frac{1}{2}$ " DEEP (MINIMUM) EVERY 10' ALONG TRIAL. NO TOOLED JOINTS ALLOWED ON MULTI-USE PATH.

DRAWN BY:
 CHECKED BY:
 APPROVED BY:
 DIRECTOR OF PUBLIC WORKS

CITY OF BOULDER, COLORADO

MULTI-USE PATH
 SECTION DETAIL

ISSUED: JULY 2, 1998
 REVISED: MAR. 15, 2022

DRAWING NO.
 2.02D